



Attestation of leak rate measurement / TA-Luft as per VDI 2440

Carl Kurt Walther GmbH & Co. KG Walther-Präzision Westfalenstraße 2 42781 Haan

Attestation No. IS-AN5-MUC-1902-100100603-001

We hereby confirm that the quick connectors listed below and produced by the above company were tested and approved according to the more stringent requirements outlined in VDI 2440. For details please see the corresponding test report, order no.: 1371849.

Product description:

Self sealing couplings of the following series:

- LP DN3 DN50
- UF DN6 DN32
- CT DN3 DN50
- BF DN5 DN50
- CN DN25 DN100

With the following characteristics in accordance with appropriate series:

Water, compressed air, various liquids, fuel, greases / oils, technical gases, hydraulic oils

Steel and brass with different surface coatings, stainless steel 1.4404 / 1.4571 / 1.4305 or equivalent

Characteristics / options:

Non-squirt feature, wide range of end connections, locking aid, ring grips for large nominal sizes, safety unlocking device

The product complies with the following requirements:

- TA-Luft (leakage requirements) as per VDI 2440, November 2000 edition
- Operating conditions:
 - Number of cycles: 5,000 / 10,000
 - Test pressure 1 bar and 10 bar
- Specified seal design

The product meets the requirements for leak measurement defined in section 5.2.6.4 of the "TA-Luft" standard.

The certificate covers leakage measurement performed on a seal as per VDI 2440 to verify tightness and/or observance of the specific leak rate defined in the "TA-Luft" standard $[\lambda \le 10^4 \, \text{mbar x l/(s x m)}]$ and extended tests under the above operating conditions.

This Attestation will be valid to February 2022.

Munich, 21st February 2016

TÜV SÜD Industrie Service GmbH Institute for Plastics

i. A. Schweizer

